



US009409032B2

(12) **United States Patent**
Brase et al.

(10) **Patent No.:** **US 9,409,032 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **SYSTEMS AND METHODS FOR MAKING
AND USING CONNECTOR ASSEMBLY
RETAINERS FOR ELECTRICAL
STIMULATION SYSTEMS**

(75) Inventors: **Randall L. Brase**, Castaic, CA (US);
Roger Evan Furgang, Simi Valley, CA
(US); **Robert R. Tong**, Valencia, CA
(US)

(73) Assignee: **Boston Scientific Neuromodulation
Corporation**, Valencia, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 884 days.

(21) Appl. No.: **13/220,332**

(22) Filed: **Aug. 29, 2011**

(65) **Prior Publication Data**

US 2012/0053646 A1 Mar. 1, 2012

Related U.S. Application Data

(60) Provisional application No. 61/378,613, filed on Aug.
31, 2010.

(51) **Int. Cl.**
A61N 1/372 (2006.01)
A61N 1/375 (2006.01)

(52) **U.S. Cl.**
CPC **A61N 1/3752** (2013.01)

(58) **Field of Classification Search**
CPC **A61N 1/3752**
USPC **607/36–38**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,181,969	B1	1/2001	Gord	
6,321,126	B1	11/2001	Kuzma	
6,516,227	B1	2/2003	Meadows et al.	
6,609,029	B1	8/2003	Mann et al.	
6,609,032	B1	8/2003	Woods et al.	
6,662,035	B2 *	12/2003	Sochor	600/378
6,741,892	B1	5/2004	Meadows et al.	
7,244,150	B1	7/2007	Brase	
7,437,193	B2	10/2008	Parramon	
7,672,734	B2	3/2010	Anderson	
7,736,191	B1 *	6/2010	Sochor	607/116
7,761,165	B1	7/2010	He	
7,949,395	B2	5/2011	Kuzma	
7,974,706	B2	7/2011	Moffitt	
8,206,180	B1 *	6/2012	Kast et al.	439/668
2005/0165465	A1	7/2005	Pianca	
2006/0030918	A1	2/2006	Chinn	

(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion, International
Application No. PCT/US2011/049594, mailed Nov. 30, 2011.

Primary Examiner — George Evanisko

(74) *Attorney, Agent, or Firm* — Lowe Graham Jones PLLC;
Bruce E. Black

(57) **ABSTRACT**

A control module for providing electrical stimulation of patient tissue includes a header disposed over an electrical interface. A connector assembly retainer is disposed in the header and coupled to the electrical interface. The connector assembly retainer includes a plurality of channels and a plurality of apertures defined at one end of the connector assembly retainer. Each of a plurality of connector assemblies is disposed in a different one of the plurality of channels of the connector assembly retainer. Each of the plurality of connector assemblies is configured and arranged for receiving a portion of a lead or lead extension and coupling the lead or lead extension to the electronic subassembly.

20 Claims, 11 Drawing Sheets

